

WHAT IS CLAIMED IS

5

1. An apparatus for reproducing video and audio, comprising:

a video decoder which receives video data coded by a unit of a first time length;

10 an audio decoder which receives audio data coded by a unit of a second time length different from the first time length;

a synchronization control unit which suspends video output of said video decoder and
15 audio output of said audio decoder, and resumes the audio output a certain time period after resuming the video output where the certain time period corresponds to a period from the suspension of the video output to the suspension of the audio output.

20

2. The apparatus as claimed in claim 1,
25 wherein the audio data coded by the unit of the second time length includes coded data with time information attached thereto and coded data with no time information attached thereto.

30

3. The apparatus as claimed in claim 2,
wherein said audio decoder notifies said
35 synchronization control unit of timings of borders of each time unit equal to the second time length by which the audio data is output.

4. The apparatus as claimed in claim 3,
wherein said synchronization control unit includes:

a counter which measures a first time
period from a time of instruction to said video
5 decoder to suspend the video output to a time of the
suspension of the audio output, and counts a second
time period equal to the first time period starting
from a time of instruction to said video decoder to
resume the video output; and

10 a unit which instructs said audio decoder
to suspend the audio output based on the instruction
to said video decoder to suspend the video output,
and instructs said audio decoder to resume the audio
output when said counter marks the second time
15 period.

20 5. The apparatus as claimed in claim 4,
wherein said counter detects the time of the
suspension of the audio output based on said timings
of borders of each time unit.

25

6. The apparatus as claimed in claim 1,
wherein a period of the suspension of the video
30 output is adjusted according to how many fields are
included in one frame of the video data.

35

7. The apparatus as claimed in claim 1,
wherein a number of fields that are repeated for

presentation during the suspension of the video output is equal to a number of fields presented during normal reproduction.

5

8. A method of reproducing video and audio, comprising the steps of:

10 outputting video data after receiving and decoding the video data coded by a unit of a first time length;

 outputting audio data after receiving and decoding the audio data coded by a unit of a second
15 time length different from the first time length;

 suspending video output and audio output;
 resuming the video output; and

 resuming the audio output a certain time
period after said resuming the video output where
20 the certain time period corresponds to a period from the suspension of the video output to the suspension of the audio output.

25

9. The method as claimed in claim 8,
wherein the audio data coded by the unit of the
second time length includes coded data with time
30 information attached thereto and coded data with no time information attached thereto.

35

10. A system for reproducing video and audio, comprising:

a video decode unit which receives video data coded by a unit of a first time length;

an audio decode unit which receives audio data coded by a unit of a second time length

5 different from the first time length;

a synchronization control unit which suspends video output of said video decode unit and audio output of said audio decode unit, and resumes the audio output a certain time period after

10 resuming the video output where the certain time period corresponds to a period from the suspension of the video output to the suspension of the audio output.